



The asbestos removal activity is regulated and sensitive due to the dangerous nature of this product. Therefore, to protect people from these risks, Polyane® has developed its unique asbestos removal range: SP ASBESTOS. These white or transparent films bring total security to the work.

White films are very opaque, which protects the site from public eyes, while providing good light transmission. The transparent films bring even more luminosity and visibility from the outside.

Whereas most market products are made from recycled material, Polyane® SP ASBESTOS is made from virgin materials providing excellent mechanical resistances, often 3 times better than other films used on the market. These products constitute a premium asbestos decontamination range.

Description	Width (m)*	Length (m)*	Surface (m ²) *	Rolls/pallet
POLYANE® SP ASBESTOS CRYSTAL	3	40	120	46
	3	80	240	23
	6	20	120	46
	6	40	240	23
POLYANE® SP ASBESTOS WHITE	3	40	120	46
	3	80	240	23
	6	40	120	46
	6	20	240	23

*: Tolerance: ± 5%

Mechanical resistance	Unit	Measures
Full film Dart test impact resistance	(gr)	≥ 1000
Longitudinal elongation to break	(%)	600*
Longitudinal break constraint	(MPa)	35**
Transversal elongation to break	(%)	600**
Transversal break constraint	(MPa)	35**



The technical characteristics noted above are indicative and can be modified at any time.